


DIGITAL FLOW METERS

Our **Digital Flow Meters** are weatherproof and also battery powered by long life battery (≈ 2 years). These attributes allow them to be installed outdoors where no external power source is available. Our flow meters can be installed in the pipeline or saddle mounted onto an existing pipe line. Units available with **Totalizer** indicate total gallons pumped. Our meters can be installed in both *PVC* and *Metal* pipelines (use saddle mount unit). Our standard flow meter is equipped with a **4 Digit Display** and our flow meter with totalizer is equipped with an **8 Digit Display**. Units can be mounted in the **Vertical** or **Horizontal Position** (please see installation instructions).

Some of the features of our **Digital Flow Meters** include *100% Waterproof, Rugged Compact Construction, Battery Powered/ No External Wiring, Weather & Chemical Spill Resistant, 1 Year Parts & Labor Warranty*. Our standard flow meter is a paddle wheel type, microprocessor-based instrument. The compact efficient design operates with negligible head loss. The range and units are preset according to your specific ordering information. Our flow meters with totalizer, both the flow rate and accumulated flow are alternately displayed on an eight digit crystal display. To distinguish between the accumulated flow and the flow rate, the word "RATE" is simultaneously displayed with the flow rate. This flow meter has all the features of the standard flow meter. Standard units are gallons per minute. Other units are available upon request.



IN-LINE MODEL



METER DISPLAY



SADDLE MOUNT MODEL

SIZE	SCH40				SCH80			
	FLOW METER		W/TOTALIZER		FLOW METER		W/TOTALIZER	
	P/N	PRICE	P/N	PRICE	P/N	PRICE	P/N	PRICE
IN LINE								
1/4"					IL-F80-0.25	\$245.00	IL-T80-1.5	\$330.00
1/2"					IL-F80-0.50	245.00	IL-T80-1.5	330.00
3/4"					IL-F80-0.75	245.00	IL-T80-1.5	330.00
1"					IL-F80-1.0	245.00	IL-T80-1.5	330.00
1-1/2"	IL-F40-1.5	\$225.00	IL-T40-1.5	\$330.00	IL-F80-1.5	240.00	IL-T80-1.5	335.00
2"	IL-F40-2.0	225.00	IL-T40-2.0	330.00	IL-F80-2.0	240.00	IL-T80-2.0	335.00
3"	IL-F40-3.0	235.00	IL-T40-3.0	335.00	IL-F80-3.0	250.00	IL-T80-3.0	340.00
4"	IL-F40-4.0	240.00	IL-T40-4.0	340.00	IL-F80-4.0	260.00	IL-T80-4.0	360.00
SADDLE MOUNT								
2"	SM-F40-2.0	245.00	SM-T40-2.0	335.00	SM-F80-2.0	245.00	SM-T80-2.0	335.00
3"	SM-F40-3.0	245.00	SM-T40-3.0	335.00	SM-F80-3.0	245.00	SM-T80-3.0	335.00
4"	SM-F40-4.0	245.00	SM-T40-4.0	335.00	SM-F80-4.0	245.00	SM-T80-4.0	335.00
6"	SM-F40-6.0	250.00	SM-T40-6.0	340.00	SM-F80-6.0	250.00	SM-T80-6.0	340.00
8"	SM-F40-8.0	255.00	SM-T40-8.0	345.00	SM-F80-8.0	260.00	SM-T80-8.0	345.00
10"	SM-F40-10	260.00	SM-T40-10	360.00	SM-F80-10	260.00	SM-T80-10	360.00
12"	SM-F40-12	260.00	SM-T40-12	360.00	SM-F80-12	260.00	SM-T80-12	360.00



LIQUID FLOW METER

MODEL	NOMINAL PIPE SIZE	FLOW (GPM)	FLOW (LPM)
565-10P	1"	5-35	20-130
565-12P	1-1/4"	10-60	40-230
565-15P	1-1/2"	20-80	75-300
565-20P	2"	30-140	115-530
565-25P	2-1/2"	40-200	150-760
565-30P	3"	80-350	230-1325
565-40P	4"	150-600	530-2270

Our **Liquid Flow Meters** are a low cost solution when you want to measure the flow rates in various sections of your facility! Each meter is manufactured of a white PVC base with a body manufactured of acrylic making these units extremely durable. Further, each meter has permanent hot-stamped markings (calibrated in gallons per minute) making this effective flow meter easy to read. We have meters available with ranges from 5 to 600 gpm and maximum pressure ratings of ≈75 psig. Consult with an **AREA Technical Representative** for sizing assistance.